

Service Information Summary

Gasoline:

Unleaded gasoline, pump octane number of 86 or higher.

Fuel Tank Capacity:

15.3 US gal (58 ℓ , 12.8 Imp gal)

Recommended Engine Oil:

API Service SJ "Energy Conserving" oil, SAE 5W-30 viscosity (see page 211).

Oil change capacity (including filter):

4.0 US qt (3.8 ℓ , 3.3 Imp qt)

Automatic Transmission Fluid:

Honda ATF-Z1 (Automatic Transmission Fluid) preferred, or a DEXRON® III ATF as a temporary replacement (see page 221).

5-speed Manual Transmission Fluid:

Honda Manual Transmission Fluid preferred, or an API service SG, SH or SJ, SAE 10W-30 or 10W-40 motor oil as a temporary replacement (see page 222).

Capacity (including differential):
1.8 US qt (1.7 ℓ , 1.5 Imp qt)

Rear Differential Fluid:

Honda Dual Pump Fluid preferred, or a DEXRON® III ATF as a temporary replacement (see page 223).

Capacity:

1.1 US qt (1.0 ℓ , 0.9 Imp qt)

Power Steering Fluid:

Honda Power Steering Fluid preferred, or another brand of power steering fluid as a temporary replacement. Do not use ATF (see page 225).

Brake Fluid:

Honda Heavy Duty Brake Fluid DOT 3 preferred, or a DOT 3 or DOT 4 brake fluid as a temporary replacement (see page 224).

Tire Pressure (measured cold):

Front/Rear:

26 psi (180 kPa , 1.8 kgf/cm²)