

## Service Information Summary

---

### **Gasoline:**

Unleaded gasoline, pump octane number of 86 or higher.

### **Fuel Tank Capacity:**

15.3 US gal (58 ℓ , 12.8 Imp gal)

### **Recommended Engine Oil:**

API Premium grade 5W-20 detergent oil (see page 247 ).

Oil change capacity (including filter):

4.4 US qt (4.2 ℓ , 3.7 Imp qt)

### **Automatic Transmission Fluid:**

Honda ATF-Z1 (Automatic Transmission Fluid) preferred, or a DEXRON® III ATF as a temporary replacement (see page 260).

### **5-speed Manual Transmission Fluid:**

Honda Manual Transmission Fluid preferred, or an API service SG, SH or SJ, SAE 10W-30 or 10W-40 motor oil as a temporary replacement (see page 261 ).

Capacity (including differential):  
2.0 US qt (1.9 ℓ , 1.7 Imp qt)

### **Rear Differential Fluid:**

Honda Dual Pump Fluid. Do not use ATF (see page 262 ).

Capacity:

1.1 US qt (1.0 ℓ , 0.9 Imp qt)

### **Power Steering Fluid:**

Honda Power Steering Fluid preferred, or another brand of power steering fluid as a temporary replacement. Do not use ATF (see page 264 ).

### **Brake Fluid:**

Honda Heavy Duty Brake Fluid DOT 3 preferred, or a DOT 3 or DOT 4 brake fluid as a temporary replacement (see page 263 ).

### **Tire Pressure (measured cold):**

Front/Rear:

26 psi (180 kPa , 1.8 kgf/cm<sup>2</sup>)