

## Air Conditioning

Refrigerant type	HFC-134a (R-134a)
Charge quantity	17.0—18.7 oz (480—530 g)
Lubricant type	SP-10

## Lights

Headlights	12 V — 60/55 W (H4/HB2)
Front turn signal/side marker lights	12 V — 21/5 W
Parking lights	12 V — 3 CP
Rear turn signal lights	12 V — 21 W
Stop/Taillights	12 V — 21/5 W
Back-up lights	12 V — 21 W
License plate light	12 V — 5 W
Ceiling light	12 V — 8 W
Spotlights	12 V — 4 CP
Cargo area Light	12 V — 8 W
Rear side marker lights	12 V — 3 CP
High-mount brake light	12 V — 21 W

## Battery

Capacity	12 V — 36 AH/5 HR 12 V — 45 AH/20 HR
----------	---

## Fuses

Interior	See page 335 or the fuse label attached to the inside of the fuse box door under the steering column.
Under-hood	See page 336 or the fuse box cover.

## Alignment

Toe-in	Front	0.0 in (0 mm)
	Rear	0.08 in (2.0 mm)
Camber	Front	0°
	Rear	— 1°
Caster	Front	1°45'

## Tires

Size	Front/Rear	P205/70R15 95S
Pressure	Front	26 psi (180 kPa , 1.8 kgf/cm <sup>2</sup> )
	Rear	26 psi (180 kPa , 1.8 kgf/cm <sup>2</sup> )